

MSDS

Material Safety Data Sheet

PERMABOND LH 050



READ MATERIAL SAFETY DATA SHEET BEFORE HANDLING PRODUCT!

Issue Date 02/17/09

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

PRODUCT NAME

MANUFACTURER

PERMABOND LH 050

PERMABOND LLC

14 Robinson Street
Pottstown, PA 19464

EMERGENCY PHONES:

MEDICAL – 1-866-827-6282

TRANSPORT - (CHEMTREC) – 1-800-424-9300

MSDS REQUESTS: HELP LINE: 1-800-640-7599

SYNONYMS

None

2. COMPOSITION/INFORMATION ON INGREDIENTS

| CHEMICAL FAMILY | COMPONENT | CAS NUMBER | CONCENTRATION (%) |
|----------------------------|--|------------|-------------------|
| Anaerobic Adhesive/Sealant | Tetraethylene glycol dimethacrylate, 85% | 109-17-1 | 30 - 60 |
| | Tetrasodium ethylenediaminetetraacetate | 64-02-8 | 1 - 5 |
| | Saccharin | 81-07-2 | 0.1 - 1 |
| | Dimethylbenzyl alcohol | 617-94-7 | 0.01 - 0.1 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

EYE IRRITANT.
SKIN IRRITANT.
SKIN SENSITIZER.

White Paste Mild, pleasant odor

| | |
|--------------|---|
| EYE | Will cause eye irritation. May cause permanent damage if eye is not immediately irrigated. |
| SKIN CONTACT | Repeated and/or prolonged contact may cause irritation and skin sensitisation. |
| INHALATION | Irritating and/or toxic vapors may be released at elevated temperatures. Unlikely to be hazardous by inhalation because of the low vapor pressure of the material at ambient temperature. |
| INGESTION | May cause nausea, vomiting and diarrhea. |

4. FIRST-AID MEASURES

| | |
|--------------|--|
| EYE | Immediately irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 minutes. Obtain immediate medical attention. |
| SKIN CONTACT | Flush exposed areas thoroughly with soap and water until all chemical is removed. Remove contaminated clothing and launder before reuse. |
| INHALATION | Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for proper medical attention. Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention. |

MSDS
Material Safety Data Sheet
PERMABOND LH 050



READ MATERIAL SAFETY DATA SHEET BEFORE HANDLING PRODUCT!

Issue Date 02/17/09

4. FIRST-AID MEASURES – CONT'D

INGESTION DO NOT induce vomiting. If individual is conscious, give milk or water to dilute stomach contents. Keep warm and quiet. Get prompt medical attention. DO NOT attempt to give anything by mouth to an unconscious person.

5. FIREFIGHTING MEASURES

| | |
|---------------------------------|---|
| AUTOIGNITION | None Established |
| FLASH POINT | 230 ∞F (Setaflash Closed Tester) |
| EXTINGUISHING MEDIA | CO ₂ ; Dry Chemical; Foam; Water Fog |
| SPECIAL FIREFIGHTING PROCEDURES | Fire fighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.; Cool exposed equipment with water spray. |
| FIRE & EXPLOSION HAZARDS | Polymerization may take place at elevated temperatures. |
| FLAMMABILITY HAZARD CLASS | 1 = Slight. |

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES Wear protective clothing. Stop leak if you can do it without risk. For small spills take up with sand or other inert absorbent material and place in a container for later disposal. Note: in bulk quantities, product absorbed on inert material may polymerize generating significant heat and pressure. Vent disposal container to prevent buildup of pressure. Can carefully solidify with anaerobic surface conditioner and dispose of as solid waste.

For safety and environmental precautions, please review entire Material Safety Data Sheet for necessary information.

7. HANDLING AND STORAGE

| | |
|---------------------|--|
| STORAGE TEMPERATURE | <= 27 ∞C 80 ∞F |
| HANDLING/STORAGE | Keep away from heat, sources of ignition and direct sunlight. Keep material refrigerated at the storage temperature referenced above. Do not freeze. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|-----------------------------|--|
| COMPONENT | EXPOSURE LIMITS |
| Saccharin | ACGIH-TWA: 10 mg/m ³ OSHA-PEL: 15 mg/m ³ ACGIH-TWA Respirable: 3 mg/m ³ OSHA-PEL Respirable: 5 mg/m ³ |
| VENTILATION REQUIREMENTS | General. |
| EYE PROTECTION REQUIREMENTS | Safety glasses, goggles or face shield to protect against splashing. |
| GLOVE REQUIREMENTS | Employee must wear appropriate protective gloves to prevent contact with this substance. |
| CLOTHING REQUIREMENTS | No special clothing required for low volume activity. |
| WASH REQUIREMENTS | Wash before eating, drinking, or using toilet facilities. |
| RESPIRATOR REQUIREMENTS | None required under normal handling conditions. Use NIOSH approved respirator if vapor or mist levels are irritating. |

MSDS
Material Safety Data Sheet
PERMABOND LH 050



READ MATERIAL SAFETY DATA SHEET BEFORE HANDLING PRODUCT!

Issue Date 02/17/09

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|----------------------------------|
| PURE SUBSTANCE OR MIXTURE | Mixture |
| PHYSICAL FORM | Paste |
| COLOR | White |
| ODOR | Mild, pleasant |
| ODOR THRESHOLD | Not available |
| MOLECULAR WEIGHT | Not applicable |
| PH AS IS | Not applicable |
| pH IN (1%) SOLUTION | Not applicable |
| OXIDIZING PROPERTIES | Not applicable |
| MELTING/FREEZING POINT | None Established |
| SOLUBILITY IN WATER | Insoluble |
| PARTITION COEFFICIENT (n-octanol/water) | None Established |
| VISCOSITY | 200000 cPs |
| SPECIFIC GRAVITY (WATER=1) | 1.07 |
| BULK DENSITY | 8.91 lb/gal |
| EVAPORATION RATE | None Established |
| VAPOR PRESSURE (mmHg) | 0.01 |
| VAPOR DENSITY (air = 1) | 1.01 |
| VOLATILES | < 1 % |
| VOLATILE ORGANIC COMPOUNDS | 0.09 lb/gal |
| AUTOIGNITION | None Established |
| FLASH POINT | 230 °F (Setaflash Closed Tester) |

10. STABILITY AND REACTIVITY

| | |
|-------------------------------------|---|
| STABILITY | Stable |
| MATERIALS TO AVOID | Metals and their salts, Permabond anaerobic surface conditioners |
| REACTIVITY HAZARD CLASS | 2 = Reactive material. |
| HAZARDOUS DECOMPOSITION PRODUCTS | Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds. |
| HAZARDOUS POLYMERIZATION CONDITIONS | Note! PERMA-LOK(R) products are anaerobic and polymerize in the absence of air. Sunlight, excessive heat, and contamination by metals or anaerobic surface conditioner in large quantities, will also cause polymerization. |

11. TOXICOLOGICAL INFORMATION

| | |
|----------------|--------------------------------------|
| ROUTE OF ENTRY | Skin Contact; Eye Contact; Ingestion |
|----------------|--------------------------------------|

CHRONIC (LONG TERM) EFFECTS OF EXPOSURE

| | |
|--------------------|---|
| TARGET ORGANS | Skin; Eyes |
| SKIN SENSITIZATION | Sensitizer. |
| CARCINOGEN | Possible cancer hazard. Risk of cancer depends on duration and level of exposure. |

MSDS
Material Safety Data Sheet
PERMABOND LH 050



READ MATERIAL SAFETY DATA SHEET BEFORE HANDLING PRODUCT!

Issue Date 02/17/09

11. TOXICOLOGICAL INFORMATION – CONT'D

| COMPONENT | ORAL TOXICITY | NOTES ON ORAL TOXICITY |
|--|--------------------------|---|
| Tetraethylene glycol dimethacrylate, 85% | | Low oral toxicity. |
| Saccharin | Oral LD50: Mouse 17 g/kg | No hazard in normal industrial use. |
| COMPONENT | DERMAL TOXICITY | NOTES ON DERMAL TOXICITY |
| Tetraethylene glycol dimethacrylate, 85% | | Irritating to the skin. Repeated and/or prolonged contact may cause skin sensitization. |
| Tetrasodium ethylenediaminetetraacetate | | Severely irritating; may cause permanent skin damage. |
| Saccharin | | Repeated and/or prolonged contact may cause skin sensitization. May cause photosensitization evidenced by repeated occurrence of dermatitic rash on exposure to sunlight. |
| COMPONENT | INHALATION TOXICITY | NOTES ON INHALATION TOXICITY |
| Tetraethylene glycol dimethacrylate, 85% | | May cause irritation to eyes and respiratory system. Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. |
| Tetrasodium ethylenediaminetetraacetate | | Vapor may be irritant to the respiratory tract. Avoid breathing vapors or mists. |
| Saccharin | | Dust is irritant to the respiratory tract. |
| COMPONENT | | NOTES ON EYE IRRITATION |
| Tetraethylene glycol dimethacrylate, 85% | | Irritating, but does not injure eye tissue. |
| Tetrasodium ethylenediaminetetraacetate | | Severe/very severe irritant. |
| Saccharin | | Particulates may scratch eye surfaces and cause mechanical irritation. |

12. ECOLOGICAL INFORMATION

| | |
|----------------------------|------------------|
| POTENTIAL TO BIOACCUMULATE | Unknown. |
| AQUATIC TOXICITY | None Established |

13. DISPOSAL CONSIDERATIONS

| | |
|--------------------------|---|
| WASTE DISPOSAL METHODS | Disposal should be in accordance with local, state or national legislation. |
| EMPTY CONTAINER WARNINGS | Empty containers may contain product residue; follow MSDS and label warnings even after they have been emptied. |

MSDS
Material Safety Data Sheet
PERMABOND LH 050



READ MATERIAL SAFETY DATA SHEET BEFORE HANDLING PRODUCT!

Issue Date 02/17/09

14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION GROUND (49CFR)

Proper Shipping Name: Unrestricted
Hazard Class or Division: None
Identification Number: None
Packing Group: None

INTERNATIONAL AIR SHIPMENT TRANSPORTATION (ICAO/IATA)

Proper Shipping Name: Unrestricted
Hazard Class or Division: None
Identification Number: None
Packing Group: None

WATER TRANSPORTATION (IMO/IMDG)

Proper Shipping Name: Unrestricted
Hazard Class or Division: None
Identification Number: None
Packing Group: None
Marine Pollutant: None

15. REGULATORY INFORMATION

USA

TSCA All components are on the TSCA inventory.

| SARA/TITLE III | CAS NUMBER | CONCENTRATION (%) |
|--|------------|-------------------|
| Saccharin (Manufacturing, no supplier notification) [1,2-Benzisothiazol-3(2H)-one,1,1-dioxide]. | 81-07-2 | 0.6 |

CALIFORNIA PROPOSITION 65

WARNING: This product contains the following chemicals that are known to the State of California to cause cancer, birth defects or other reproductive harm:

| COMPONENT | CAS NUMBER |
|-----------|------------|
| SACCHARIN | 81-07-2 |

16. OTHER INFORMATION

MSDS DATE 02/17/09

This MSDS contains change from the previous one in section 1; Update on Manufacturer Address

FOR INFORMATION CONTACT: Permabond LLC
HELP Line: 1-800-640-7599

ADDITIONAL INFORMATION: The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guaranty of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.